

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number  
**WO 2005/045969 A2**

(51) International Patent Classification<sup>7</sup>: **H01M 8/02**, 8/24

(21) International Application Number:  
PCT/JP2004/015675

(22) International Filing Date: 15 October 2004 (15.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003-380159 10 November 2003 (10.11.2003) JP  
2004-029770 5 February 2004 (05.02.2004) JP

(71) Applicant (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA** [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **TAKASE, Hironari** [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). **TSUGANE, Takahide** [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1,

Toyota-cho, Toyota-shi, Aichi 4718571 (JP). **KIKUCHI, Yoshiaki** [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). **SUZUKI, Hiroshi** [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP).


(74) Agent: **ITEC INTERNATIONAL PATENT FIRM**; Pola-Nagoya Bldg., 9-26, Sakae 2-chome, Naka-ku, Nagoya-shi, Aichi 4600008 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: FUEL CELL, DISASSEMBLY METHOD THEREOF, AND SEPARATORS USED THEREIN



(57) Abstract: A disassembly procedure of a fuel cell (10) places a sloped edge of a cracking tool (12) on a bottom of a recess (11). The procedure subsequently sets the bottom of the recess (11) as a point of application, an opening edge of the recess (11) where a flat side of the cracking tool (12) is placed, as a point of support, and a base end of the cracking tool (12) where a force is applied, as a point of power, and applies an external force to the point of application by the principle of leverage. A crack goes from the point of application towards a position outside electrodes (4 and 5) of an MEA (2) but inside a sealing members (8). The procedure then removes the broken separator (6) to expose the MEA (2) outside and cuts off an electrolyte membrane (3) along a cut line CL outside the electrodes (4 and 5) but inside the sealing members (8).



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— *without international search report and to be republished upon receipt of that report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*